



ISO 8020

Ståltipe: HSS ~1.3343

Skaft 60 - 62 HRc

Hoved 40 - 50 HRc

Bestillingsnr.: LOK Ø x L x Form

Spørg om pris

Ø	d2	K	r	L	L	L	L
d1 TOL h6	+0/-0,15	+0,2/-0,1	+0,1/0	71 mm	80 mm	100 mm	130 mm
0,6 - 0,9					-	-	-
1,0 - 1,9					-	-	-
2,0 - 2,9	5,0						-
3,0 - 3,9	5,0	3,0 (5)					
4,0 - 4,9	6,0						
5,0 - 5,9	8,0						
6,0 - 6,9	9,0						
7,0 - 7,9	10,0		0,30				
8,0 - 8,9	11,0						
9,0 - 9,9	12,0						
10,0 - 10,9	13,0						
11,0 - 11,9	14,0						
12,0 - 12,9	15,0						
13,0 - 13,9	16,0						
14,0 - 14,9	17,0	5,0					
15,0 - 15,9							
16,0 - 16,9	19,0						
17,0 - 17,9							
18,0 - 18,9							
19,0 - 19,9			0,4				
20,0 - 20,9	23,0						-
21,0 - 21,9							-
22,0 - 22,9							-
23,0 - 23,9							-
24,0 - 24,9							-