



DIN 1530

Skaft : 60-62 HRC

Hoved: 40-50 HRC

Mat.: WS-1.2067

Bestillingsnr.: UDST-Ø x L-D

d1 TOL g6	d2 0/-0,02	K +0,2/0	r	Pris				
				L				
				100	125	160	200	250
1,0-1,9	1,8-2,8	1,19-1,28	0,4 +0,3/0					
2,0	3,0	1,37						
2,2	3,2	1,37						
2,5	3,5	1,37	0,6 +04/0					
2,7	4,0	1,63						
3,0	4,5	1,80						
3,2	4,5	1,63						
3,5	5,0	1,80						
4,0	5,5	1,80						
4,2	5,5	1,63						
4,5	6,0	1,80						
5,0	6,5	1,80						
5,2	6,5	1,63						
5,5	7,0	1,80	1,0 +0,5/0					
6,0	8,0	2,23						
6,2	8,0	2,06						
6,5	9,0	3,17						
7,0	9,0	2,73						
8,0	10,0	2,73						
8,2	10,0	2,56						
8,5	11,0	3,17						
9,0	11,0	2,73						
10,0	12,0	2,73						
12,0	14,0	2,73						
14,0	16,0	3,23						
16,0	18,0	3,23						